

KELVIN **Clim A12**

Cooling capacity: 12 ~ 37 kW




Air cooled liquid chillers with scroll compressors, plate heat exchangers and plug fan

KELVIN Clim A12

KELVIN Clim A12: Air cooled liquid chillers for indoor installation, equipped with scroll compressor and plug fan
Cooling Capacity: 12 ~ 37 kW



KELVIN AIR CONDITIONING



MAIN FEATURES

- Air cooled liquid chiller.
- 9 models available, for a wide selection opportunity.
- Average step of 3kW.
- EER up to 2,65.
- ESEER up to 3,25.
- Scroll compressors.
- R410A Refrigerant charge.
- Single refrigerant circuit.
- Plate type heat exchangers.
- Plug fan EC.
- Pumping group on board.
- Single air circuit.
- Suitable for indoor installation.

MAIN BENEFITS

- Availability of kit for the reduction of the noise.
- Availability of partial heat recovery system.
- Plug fan EC for an high efficiency.
- Easily of maintenance.
- Eurovent Certification. (pending)

FANS WITH BRUSHLESS TYPE EC MOTOR

The fans electric motors are the brushless type with built-in electronic commutation system (EC) which yield high energy savings during operation in reduced air flow. These electric motors are ensuring high performances, minimum energy consumption and total absence of electromagnetic noise.

INDOOR INSTALLATION

The machines are designed for indoor installation and ducting for air suction and discharge. For outdoor installation the use of the dedicated optional kit is mandatory. The machine must be installed under a cover or anyway protected against atmospheric agent.

WORKING LIMITS IN COOLING MODE

Chilled water outlet temperature: -12~20°C
 Ambient temperature: -10~45°C



MAIN COMPONENTS

FRAMEWORK

- Base, self supporting frame and panelling in steel plate with protective surfaces treatment in compliance with UNI ISO 9227/ASTMB117 and ISO 7253, and painted with epoxy powders.
- Colour: RAL 9002

COMPRESSORS

- Orbiting spiral (SCROLL) hermetic compressors with spiral profile optimized for R410A refrigerant.
- ON / OFF capacity control (0 / 100% each compressor).
- 2-pole 3-phase electric motor with direct on line starting.
- Crankcase heater.
- Electric motor thermal protection via internal winding temperature sensors.
- Terminal box with IP54 enclosure class.
- Rubber supports.

EVAPORATOR

- Copper brazed plate type with cover plates, plates and connections in AISI 316 stainless steel:
- Anticondensate insulation made of neoprene.
- Temperature sensors on water inlet and outlet.
- Differential water pressure switch for water flow control.
- Antifreeze heater.

CONDENSING COIL

- Heat exchanger coil with copper tubes and high efficiency aluminium fins, specifically developed to provide high heat transfer and lower pressure drops.
- Frame in galvanized steel.

FANS SECTION

- Centrifugal fans with backward curved blades, single suction and without scroll housings (Plug-fan).
- Brushless type synchronous EC motor with integrated electronic commutated system and continuous variation of the rotation speed. The motor rotation control is obtained with the EC system (Electronic Commutation) that manage the motor according to the 0~10V proportional signal coming from the microprocessor control.
- Maintenance-free bearings
- IP54 enclosure class.

HYDRAULIC ASSEMBLY

- Pumping group with 1 pump, 2 poles electric motor.
- Expansion tank.
- Safety valve.
- Manual filling assembly.
- Pressure gauge.

REFRIGERANT CIRCUIT

- Thermostatic expansion valve.
- Sight glass.
- Filter dryer on liquid line.
- Safety valve on high and low pressure side.
- Pressure transducers with indication, control and protection functions, on low and high refrigerant pressure.
- R410A refrigerant charge.
- Sight glass.
- Filter dryer on liquid line.
- Safety valve on high and low pressure side.
- Pressure transducers with indication, control and protection functions, on low and high refrigerant pressure.
- R410A refrigerant charge.

ELECTRICAL PANEL

- In accordance with EN60204-1 norms complete with:
- Main switch with door lock safety from model T19 included.
 - Contactors for compressor.
 - Transformer for auxiliary circuit and microprocessor supply.
 - Panel with machine controls.
 - Power supply: 230/1/50 for M models.
 - Power supply: 400/3/50+N for T models.

CONTROL SYSTEM

- Microprocessor control. The system includes:
 - Display for the visualization of the alarm codes, set values and temperature values.
 - Dynamic set point.
 - Compressor running hour meter.
 - Contact for general alarm remotization.
 - "Low Temperature" set for operation with chilled water production up to -8°C.
 - Menu with protection password.

OPTIONAL ACCESSORIES

KELVIN Clim A12 SIZE	T 13 P1 C0	T 15 P1 C0	T 18 P1 C0	T 22 P1 C1	T 24 P1 C1	T 28 P1 C1	T 32 P1 C1	T 36 P1 C1	T 42 P1 C1
150 - LNO kit (noise reduction)	•	•	•	•	•	•	•	•	•
172 - Rubber support (kit)	•	•	•	•	•	•	•	•	•
450 - Partial heat recovery	•	•	•	•	•	•	•	•	•
251 - Coils protection nets	•	•	•	•	•	•	•	•	•
920 - Remote control kit	•	•	•	•	•	•	•	•	•
923 - Kelvin-Com MBUS/JBUS Serial board	•	•	•	•	•	•	•	•	•
460 - Kit for outdoor installation	•	•	•	•	•	•	•	•	•
962 - Kit modem GSM	•	•	•	•	•	•	•	•	•
957 - Plantwatch without modem	•	•	•	•	•	•	•	•	•
930 - Remote graphic terminal kit	•	•	•	•	•	•	•	•	•
889 - Master Plant SEQUENCER	•	•	•	•	•	•	•	•	•
Kelvin CLOUD PLATFORM	•	•	•	•	•	•	•	•	•

• available accessory; - not available accessory

TECHNICAL DATA KELVIN Clim A12


KELVIN Clim A12		T 13 P1	T 15 P1	T 18 P1	T 22 P1	T 24 P1	T 28 P1	T 32 P1	T 36 P1	T 42 P1		
SIZE		C0	C0	C0	C1	C1	C1	C1	C1	C1		
STANDARD	Cooling capacity (1)	kW	12,6	14,5	16,7	19,2	21,8	25,5	28,8	31,8	36,6	
	Unit power input	kW	5,0	6,0	6,9	7,2	8,4	10,2	11,4	13,1	15,9	
	Evaporator water flow rate	m³/h	2,2	2,5	2,9	3,3	3,8	4,4	5,0	5,5	6,3	
	Evaporator pressure drop	kPa	27	36	29	27	35	37	29	35	36	
	Compressors		scroll	scroll	scroll	scroll	scroll	scroll	scroll	scroll	scroll	
	Quantity	n.	1	1	1	1	1	1	1	1	1	
	Capacity steps	n.	1	1	1	1	1	1	1	1	1	
	Centrifugal fans EC	n.	1	1	1	1	1	1	1	1	1	
	Total air flow	m³/h	4000	4800	5500	6500	7000	8500	10000	11000	12000	
	External static pressure	Pa	50	50	50	50	50	50	50	50	50	
	Air circuits	n.	1	1	1	1	1	1	1	1	1	
	Refrigerant		R410A	R410A	R410A	R410A	R410A	R410A	R410A	R410A	R410A	
	Total refrigerant charge (optional excluded)	kg	3,2	3,2	3,3	5,3	5,3	5,3	5,5	5,6	5,6	
	Gas circuits	n.	1	1	1	1	1	1	1	1	1	
	Power supply	V/Ph/Hz	50/3/50	400/3/50	400/3/50	400/3/50	400/3/50	400/3/50	400/3/50	400/3/50	400/3/50	
	Max unit operating current (FLA)	A	18,1	21,4	21,4	26,4	31,6	32,7	36,4	42,7	45,9	
	Unit starting current (LRA)	A	69,4	80,4	106,4	104,1	120,1	127,1	127,7	149,7	183,7	
	EER (1)	kW/kW	2,53	2,43	2,41	2,65	2,58	2,51	2,52	2,43	2,30	
	ESEER		3,16	3,02	3,01	3,25	3,18	3,13	3,18	3,01	2,79	
	Sound power level [Lw] (2)	dB(A)	85,2	89,2	92,2	87,1	88,7	92,9	92,1	94,2	96,0	
	Average sound pressure level [Lpm] (3)	dB(A)	69,5	73,4	76,4	70,6	72,1	76,3	75,6	77,6	79,4	
	Net weight	kg	249,8	249,8	264,8	361,5	361,5	371,5	370,0	375,0	380,0	
	Hydraulic connections											
	Evaporator IN/OUT - ISO 1/7 - R	Ø	2/1 1	"2/1 1	"2/1 1	"2/1 1	"2/1 1	"2/1 1	"1	"1	"1"	
	Pumping group											
	1 pump - 2 poles electric motor	kW	0,5	0,5	0,5	1,0	1,0	1,0	1,0	1,0	1,0	
	OPT	Partial heat recovery (4)										
		Heating capacity	kW	4,6	5,3	6,1	7,0	8,0	9,4	10,6	11,7	13,4
	LNO KIT %100	Cooling capacity (1)	kW	12,6	14,5	16,7	19,2	21,8	25,5	28,8	31,8	36,6
		Unit power input	kW	5,0	6,0	6,9	7,2	8,4	10,2	11,4	13,1	15,9
		Total air flow	m³/h	4000	4800	5500	6500	7000	8500	10000	11000	12000
		External static pressure	Pa	50	50	50	50	50	50	50	50	50
		EER (1)	kW/kW	2,53	2,43	2,41	2,65	2,58	2,51	2,52	2,43	2,30
		Sound power level [Lw] (2)	dB(A)	85,2	89,1	92,1	87,1	88,7	92,8	92,1	94,1	96,0
	Average sound pressure level [Lpm] (3)	dB(A)	69,4	73,4	76,4	70,5	72,1	76,2	75,5	77,5	79,4	
	LNO KIT %85	Cooling capacity (1)	kW	12,2	14,1	16,2	18,7	21,2	24,7	27,9	30,9	35,4
		Unit power input	kW	5,2	6,2	7,2	7,5	8,8	10,6	11,8	13,5	16,5
		Total air flow	m³/h	3400	4080	4675	5525	5950	7225	8500	9350	10200
External static pressure		Pa	36	36	36	36	36	36	36	36	36	
EER (1)		kW/kW	2,35	2,27	2,24	2,48	2,42	2,34	2,36	2,29	2,14	
Sound power level [Lw] (2)		dB(A)	81,3	85,3	88,3	83,6	85,2	89,3	88,6	90,6	92,5	
Average sound pressure level [Lpm] (3)	dB(A)	65,6	69,5	72,5	67,0	68,6	72,7	72,0	74,0	75,9		
LNO KIT %70	Cooling capacity (1)	kW	11,6	13,5	15,5	17,9	20,3	23,6	26,7	29,5	33,8	
	Unit power input	kW	5,5	6,6	7,7	7,9	9,3	11,1	12,5	14,2	17,3	
	Total air flow	m³/h	2800	3360	3850	4550	4900	5950	7000	7700	8400	
	External static pressure	Pa	25	25	25	25	25	25	25	25	25	
	EER (1)	kW/kW	2,12	2,06	2,02	2,26	2,19	2,12	2,13	2,08	1,95	
	Sound power level [Lw] (2)	dB(A)	76,8	80,7	83,6	79,4	81,0	85,1	84,4	86,4	88,3	
Average sound pressure level [Lpm] (3)	dB(A)	61,0	64,9	67,9	62,8	64,4	68,5	67,8	69,8	71,7		

1. Referred to chilled water temperature 12/7°C – 0% glycol solution; air temperature to the condenser 35°C. Fouling factor of the exchangers 0,043 m²K/kW.
2. Sound power level [Lw] according to ISO EN 2 – 9614.
3. Average sound pressure level [Lpm] 1m far according to ISO EN 3744.
4. Referred to chilled water temperature 12/7°C – 0% glycol solution; air temperature to the condenser 35°C; water temperature heat recovery 40/45°C – 0% glycol solution. Fouling factor of the exchangers 0,043 m²K/kW.

DIMENSIONS (mm)

KELVIN Clim A12

SIZE C			
	a	b	c
C0	1108	760	1460
C1	1250	890	1950



● Note

● Note

